### CGA COMPRESSED GAS SERVICE CYLINDER CONNECTIONS



PART NUMBER

CAP-30BR-P

CAP-30BR-PR

CAP-30BR-TCR

#### **CONNECTION NO. 320**

PRESSURES UP TO 3000 PSI


CYLINDER VALVE OUTLET **RIGHT HAND** MALE

BRASS W/ POLY DISC LESS RING & CHAIN

BRASS W/ TEFLON CALCIUM FILLED DISC

DESCRIPTION

BRASS W/ POLY DISC



DUST CAPS

INLET CONNECTION **RIGHT HAND** FEMALE NUT, NIPPLE & GASKET

## **CONNECTION NO. 320 CYLINDER VALVE OUTLET CAPS**

L

0.54"

0.54"

0.54"

HEX

All dimensions are in inches - for reference only, subject to change.

CAP-30CH-PR	NICKEL PLATED BRAS	s w/ Poly dis	0.54"						
CAP-30SS-PR	303 STAINLESS STEE	L W/ POLY DIS	C		0.54"	And the state of t			
CAP-30SS-TCR	303 STAINLESS STEEL W/ TEFLON CALCIUM FILLED DISC				0.54"	3.75"			
GASKETS									
PART NUMBER	DESCRIPTION	D	H	W					
GSK-32-T	VIRGIN PTFE	.703	.250	.094					
GSK-32-K	VIRGIN PCTFE	.703	.250	.094		T L L			


# INLETS X 1/4" MALE NATIONAL PIPE THREAD (INCLUDES NUT, NIPPLE & PTFE GASKET)

PART NUMBER	DESCRIPTION	L	BRASS OR NICKEL PLATED	94"
INL-320BR-4M-48	BRASS	3.00"	BRASS NUT, NIPPLE &	.176"
INL-CV320BR-4M	BRASS W/ CHECK VALVE	3.00"	GASKET	
INL-320CH-4M-48	NICKEL PLATED BRASS	3.00"		
INL-CV320CH-4M	NICKEL PLATED BRASS W/ CHECK VALVE	3.00"		L
INL-320SS-4M-28	STAINLESS STEEL	1.75"	STAINLESS STEEL	← .94" ← .11/8" HEX Ø.176" ¬
INL-320SS-4M-40	STAINLESS STEEL	2.50"	303 NUT, 316L NIPPLE &	-1 1/8" HEX Ø.1/8"
INL-320SS-4M-48	STAINLESS STEEL	3.00"	GASKET	
INL-320SS-4M-56	STAINLESS STEEL	3.50"	OPTIONAL INTEGRAL	
INL-320SS-4M-70R	STAINLESS STEEL W/ FILTER	4.375"	CHECK VALVE	
INL-CV320SS-4M	STAINLESS STEEL W/ CHECK VALVE	2.50"		<del>-</del> L"

# INLETS X 1/4 MALE FACE SEAL (INCLUDES 303 SS NUT, 316L SS NIPPLE & PCTFE GASKET)

PART NUMBER	DESCRIPTION	L
INL-320SS-4MFS-28	STAINLESS STEEL 12 Ra	1.75"
INL-320SS-4MFS-P	STAINLESS STEEL 9 Ra EP	1.75"

EP = Electropolished ID



# 1/8" HEX Ø.180''

INLETS X ORBITAL TUBE WELD STUB (INCLUDES SILVER PLATED 303 SS NUT, 316L SS NIPPLE & PCTFE GASKET) PART NUMBER DESCRIPTION L Т INL-320SS-4TS-28F 1.75" 1/4"0D X .035" WALL STAINLESS STEEL 12 Ra\* 91 1 1/8" HEX INL-320SS-4TS-P **STAINLESS STEEL 9 Ra EP\*** 1.75" 1/4"0D X .035" WALL INL-CV320SS-4TS STAINLESS STEEL W/ CHECK VALVE 2.47" 1/4"0D X .035" WALL INL-320SS-6TS-30F STAINLESS STEEL 12 Ra 1.875" 3/8"0D X .035" WALL INL-320SS-6TS-P **STAINLESS STEEL 9 Ra EP** 1.875" 3/8"0D X .035" WALL INL-320SS-8TS-30F STAINLESS STEEL 12 Ra 1.875" 1/2"0D X .049" WALL \*PTH-7 Pigtail Handle available EP = Electropolished ID INL-320SS-8TS-P STAINLESS STEEL 9 Ra EP 1.875" 1/2"0D X .049" WALL



GasFlo Products Inc. CGA Compressed Gas Service Cylinder Connections are Manufactured to CGA V-1 Standards Additional materials and configurations available on request. Minimum order quantities may be required.

40 Green Pond Road, Rockaway, NJ 07866 Phone: 973-276-9011 Fax: 973-276-9014 www.gasflo.com

MADE IN USA CGA320-2017 Rev. A

Available with Check Valve upon request

Member Compressed Gas Association

GASFLOPRODUCTS


©GasFlo Products, Inc. 2025





©GasFlo Products, Inc. 2025

PRESSURES UP TO 3000 PSI



Member Compressed Gas Association